



蒸發器 - 冷藏

型號 MODEL	規格 Spec.	傳熱面積 Trans. Area mf	冷凍能力 Capacity TD 7°C Kcal/Hr	風扇馬達 Fan Motor				外型尺寸 Dim.(mm)			吊掛孔		冷煤配管 Refr. Connect		重量 Weight 公斤 Kg
				直徑 Dia.	數量 NO.	風量 CMM	電流 A	長 L	寬 W	高 H	寬 C	深 D	入口 Inlet	出口 Outlet	
EVR4-0060-112	60尺	7.34	1,541	12"	1	32	0.4	706	370	420	490	440	1/2"	3/4"	18.4
EVR4-0080-212	80尺	9.71	2,039	12"	2	52	0.8	1,008	370	420	792	440	1/2"	7/8"	25.0
EVR4-0100-212	100尺	12.13	2,547	12"	2	52	0.8	1,008	370	420	792	440	1/2"	7/8"	27.4
EVR4-0120-212	120尺	14.54	3,053	12"	2	60	0.8	1,160	370	420	944	440	1/2"	7/8"	29.5
EVR4-0120-312	120尺	14.54	3,053	12"	3	80	1.2	1,310	370	420	1094	440	1/2"	7/8"	34.2
EVR4-0120-214	120尺	14.56	3,058	14"	2	82	2.0	1,008	370	500	792	440	1/2"	7/8"	38.2
EVR4-0140-312	140尺	16.93	3,555	12"	3	83	1.2	1,310	370	420	1094	440	1/2"	7/8"	34.5
EVR4-0140-214	140尺	16.88	3,545	14"	2	86	2.0	1,160	370	500	944	440	1/2"	7/8"	31.3
EVR4-0160-312	160尺	19.34	4,061	12"	3	84	1.2	1,462	370	420	1246	440	1/2"	1-1/8"	35.1
EVR4-0160-214	160尺	19.36	4,066	14"	2	87	2.0	1,310	370	500	1094	440	1/2"	1-1/8"	35.0
EVR4-0180-312	180尺	21.76	4,570	12"	3	88	1.2	1,386	400	500	1170	470	1/2"	1-1/8"	36.0
EVR4-0180-216	180尺	21.76	4,570	16"	2	90	2.4	1,386	400	500	1170	470	1/2"	1-1/8"	37.1
EVR4-0200-216	200尺	24.12	5,065	16"	2	92	2.4	1,510	400	500	1294	470	1/2"	1-1/8"	43.2
EVR4-0225-216	225尺	27.16	5,704	16"	2	93	2.4	1,670	400	500	1454	470	1/2"	1-1/8"	46.0
EVR4-0225-314	225尺	27.16	5,704	14"	3	118	3.0	1,670	400	500	1454	470	1/2"	1-1/8"	48.0
EVR4-0250-314	250尺	30.21	6,344	14"	3	120	3.0	1,830	400	500	1614	470	1/2"	1-1/8"	51.5
EVR4-0300-316	300尺	36.21	7,604	16"	3	160	3.6	1,805	400	620	1549	470	5/8"	1-3/8"	60.1
EVR4-0360-316	360尺	43.43	9,120	16"	3	170	3.6	2,108	400	620	1852	470	5/8"	1-3/8"	67.6
EVR4-0400-416	400尺	48.24	10,130	16"	4	190	4.8	2,310	400	620	2054	470	5/8"	1-3/8"	72.4
EVR4-0450-318	450尺	54.17	11,376	18"	3	230	4.8	2,180	500	740	1934	600	5/8"	1-3/8"	103.4
EVR4-0500-318	500尺	60.16	12,634	18"	3	232	4.8	2,390	500	740	2144	600	5/8"	1-3/8"	110.9
EVR4-0560-318	560尺	67.69	14,215	18"	3	230	4.8	2,180	500	740	1934	600	7/8"	1-5/8"	126.1
EVR4-0600-320	600尺	72.33	15,189	20"	3	270	4.8	2,310	500	740	2064	600	7/8"	1-5/8"	135.7
EVR4-0675-320	675尺	81.21	17,054	20"	3	270	4.8	2,180	500	740	1934	600	7/8"	1-5/8"	146.5
EVR4-0750-320	750尺	90.20	18,942	20"	3	270	4.8	2,390	500	740	2144	600	7/8"	1-5/8"	158.4
EVR4-0810-324	810尺	97.48	20,471	24"	3	360	6.6	2,560	550	740	2314	650	7/8"	1-5/8"	165.3
EVR4-0900-324	900尺	108.19	22,720	24"	3	360	6.6	2,810	550	740	2564	650	7/8"	2-1/8"	180.0
EVR4-1000-324	1000尺	120.20	25,242	24"	3	360	6.6	2,810	550	820	2564	650	7/8"	2-1/8"	197.5
EVR4-1200-324	1200尺	144.24	30,290	24"	3	360	6.6	2,810	550	970	2564	650	7/8"	2-1/8"	228.5
EVR4-1350-420	1350尺	162.23	34,068	20"	4	360	6.4	3,130	550	970	2884	650	7/8"	2-1/8"	
EVR4-1600-420	1600尺	192.27	40,377	20"	4	360	6.4	3,130	600	900	2884	700	7/8"	2-1/8"	
EVR4-1800-424	1800尺	216.62	45,490	24"	4	480	8.8	3,130	600	970	2884	700	7/8"	2-1/8"	
EVR4-1950-424	1950尺	234.67	49,281	24"	4	480	8.8	3,130	600	1050	2884	700	7/8"	2-1/8"	